

Ultrasky Flat Skylight Features

- Distinctive Frameless Glass
- Fully insulated core
- Unique click-fit installation
- Noise reducing glass
- Overall U-value of 1.2

FEATURES

- 1 Edge to Edge glass for a contemporary look.
- 2 Fineline plasterboard trim for a neat internal finish.
- 3 Slim aluminium surround blends seamlessly with glass.
- 4 Fully insulated frame with Warm Frame technology.
- 5 Click-fit clips for quick fitting first time, every time.
- 6 Noise reducing glass reduces noise by up to 34dB.
- 7 Double seal gaskets with high compression, so seal won't degrade over time.



Kerb Features

Factory assembled for an easy fit

Fully reinforced

Insulating chambered black PVCu

Watertight welded frame

FEATURES


- 1. 4° pitch for optimum performance.
- 2. Weathering tape for double waterproofing on joints.
- 3. Self-aligning internal reinforcement for fast installation
- 4. Tilt fillet for optimum membrane run off.
- 5. Fully welded mitred frame means you can install the skylight and waterproof it later.



Please note kerbs can be delivered separately if required at an extra £50 per kerb.

Please note (if customer supplying own kerb)

The kerb width must be 70mm.



The minimum height of the kerb must be 150mm at it's lowest point. The kerb must have a pitch of 4° .

